

Technical Datasheet Variostep Classic



Kronoflooring GmbH Mühlbacher Straße 1 01561 Lampertswalde/Germany Ph. +49 3522 33 30 • Fax: +49 3522 33 399 info@kronoflooring.com

Made by Kronospan

Direct Pressure Laminate, Level of use according to EN 13329: class 23/32 - AC4







General commercial use

The guarantee applies to the living area according to warranty regulations*

		งร	

dimension	thickness (d)	8 ± 0,50 mm · dmax - dmin ≤ 0,50 mm			
length			1285 ± 0,50 mm		
	width (b)	b) 192 ± 0,10 mm · b		bmax - bmin ≤ 0,20 mm	
profile	long side	twin clic	short side	1clic 2go pure	
groove	long side	real groove	short side	real groove	

TOLERANCE

TOLLIVANOL		
squareness	EN 13329	≤ 0,20 mm
straightness	EN 13329	≤ 0,30 mm
flatness crosswise	EN 13329	concave: ≤ 0,15% · convex: ≤ 0,20%
flatness length	EN 13329	concave: ≤ 0,50% · convex: ≤ 1,00%
gaps between elements	EN 13329	average: ≤ 0,15 mm · max: ≤ 0,20 mm
height difference between elements	EN 13329	average: ≤ 0,10 mm · max: ≤ 0,15 mm
misalignment		± 2 mm

TEST

abrasion resistance		EN 13329	AC4 (≥ 4000 rpm)	
impact resistance		EN 13329	small ball ≥ 12 N · big ball ≥ 750 mm	
stain resistance	group 1 & 2	EN 13329	grade 5	
Stair resistance	group 3		≥ grade 4	
castor chair test		EN 13329	no change in appearance or damage, as defined per EN 425	
effect of a furniture leg		EN 13329	no damage shall be visible, when testet with foot type 0	
thickness swelling		EN 13329	≤ 18%	
static indentation		EN 13329	≤ 0,05 mm	
light fastness		EN 13329	grey scale ≥ 4 at blue wool grade 6	
dimensional variations after changes in relative humidity		EN 13329	lengthwise ≤ 0,9 mm · crosswise ≤ 0,9 mm	
locking strength		EN 13329	length ≥ 1 kN/m · width ≥ 2 kN/m	
surface soundness		EN 13329	≥ 1,25 N/mm²	

ENVIRONMENT

emission of formaldehyde	EN 16516	class E1

PHYSICAL BEHAVIOR

FIT SICAL BEHAVIOR			
fire behavior	EN 13501-1	Cfl s1	
slide resistance	EN 13893	technical class DS	
thermal resistance	EN 12667	0,073 (m ² K)/W ± 15%	
thermal conductivity	EN 12664	0,110 W/(m*K) ± 15%	

^{*}Detailed warranty conditions are available at www.krono-original.com

For further information, please see: www.blauer-engel.de